

PROTECTAMESH™ HD
Rockshield

T: +44 (0)1621 874200
F: +44 (0)1621 874299

Product Data Sheet

Composition:

Low density polyethylene, diamond mesh with carbon black and blowing agent.

Mesh Mechanical properties (Mean values)

Tensile Strength (MD)	ASTM D4595	kN/m	7.8
Elongation @ max strength (MD)	ASTM D4595	%	139
Elongation @ max strength (TD)	ASTM D4595	%	110
Tear strength (MD)	ASTM D624	N	66
Tear strength (TD)	ASTM D624	N	72
Impact strength	ASTM G14 (spherical)	N	78
Impact resistance	ASTM G13 (MOD)		No failure at 6" rock
Compressive strength	ASTM D1621 (MOD)		90 psi at 50% reduction
Cathodic protection			No inhibiting effect
Physical properties (Typical values)			
Thickness		mm	10
Mesh Count			28 in 20cm
Weight per m ²		g	1550
Aperture size		mm	4 x 4
Roll dimensions			
Roll Width		m	1.22, 1.53, 1.83
Roll length		m	As required

As part of its continual improvement process Fiberweb Geosynthetics Ltd reserve the right to change the properties listed on this data sheet without prior notice.

TM indicates a trade mark of Fiberweb plc or a Fiberweb Group company, many of which are registered in a number of countries around the world.